

DERZ PLUS

Cement-based, reinforced with special hydrophobic polymer additives, flexible joint filler-material for 1-6 mm joint gaps.

■ ADVANTAGES

- Easy to prepare and apply.
- High pressure and abrasion resistance.
- The resistance to fouling and cracking is very high.
- It adheres well to the surface where it is applied. It offers a smooth surface.
- It is resistant to freezing and thawing cycle.

■ SCOPE OF APPLICATION

- It is used in interior joint applications up to 6 mm wide on coatings such as ceramics, granite, tiles, marble and natural stone.

■ WARNINGS AND RECOMMENDATIONS

- Before joint application, dust, sawdust, construction cement residues that may be present between the joint cavities must be cleaned
- Before the application, the joint gaps should be moistened with the help of a sponge.
- It should be ensured that the coatings are applied at least before 24 hours, and the ceramic glue is hardened.
- It is not applied on metal surfaces.
- Foreign materials should never be added.
- In outdoor applications, the application should not be made in cases where there is a possibility of rainfall.
- (+ 5 °C) - (+ 35 °C) degree application is recommended.
- All tools used after the application should be washed with water before drying.

■ STORAGE

Packaging	20 kg Kraft Bag
Colour	White
Shelf Life	1 year from date of manufacture when stored unopened and undamaged in a dry, moisture-free environment. Packages should be kept tightly closed when not in use.

■ CONSUMPTION

Depending on the joint width and ceramic size, 100 – 800 gr/m²

■ APPLICATION FEATURES

- DryFiX DERZ PLUS joint filling is slowly added to 6,75-7,25 lt water and mixed for 2-3 minutes with the help of a mixer. After resting for 5 minutes, it is mixed again for 1-2 minutes.
- The prepared mixture should be used within 30 minutes.
- The mortar is filled into the joint gaps with rubber trowels and the excess is removed by stripping.
- Depending on the weather conditions, it is cleaned after an average of 15-20 minutes with a wet sponge without putting much pressure on the surface.

All technical information stated in this product data sheet is based on laboratory tests.
Actual values may vary due to circumstances beyond our control.

İZERSAN YAPI MALZ.SAN VE TİC.LTD.ŞTİ.

Center Factory: Egemenlik Mah. 6016/6 Sk. No:19/1 Işikkent Bornova/ İZMİR

www.dryfix.com.tr - info@izersan.com.tr

Tel&Fax: +90 850 777 05 35



DERZ PLUS

■ TECHNICAL SPECIFICATIONS AND PERFORMANCE VALUES

Colour	White
Water Ratio	6,75-7,25 lt / 20 kg
Opening Time	Min. 24 hours
Duration of the mortar	Max. 30 min
Flexural Strength	≥ 2.5 N/mm ²
Compressive Strength	≥ 15 N/mm ²
Water Intake 30 min/ 240 min	≤ 5 gr/ ≤ 10 gr
Shrinkage Coefficient	≤ 3 mm/m
Abrasion Resistance	≤ 2000 mm ³

The specified periods are valid at 20°C surface and ambient temperature, the time is prolonged at low temperature, the time is shortened at high temperature. DRYFIX is not responsible for application errors that may occur if the product is used outside its purpose or if the application conditions and recommendations specified above are not complied with.

■ SAFETY PRECAUTIONS

During use and storage, appropriate work clothes, glasses, gloves and masks should be used for worker health and safety. Eye, mouth and skin contact should be avoided. The contacted area should be washed with plenty of water. In more dangerous situations or if the product is swallowed, a specialist doctor should be consulted immediately. Food and drink should not be allowed into application areas. It should be kept out of reach of children. For detailed information, the Safety Data Sheet (SDS) should be consulted.

■ LEGAL WARNING

Applications that may occur if the product is used for purposes other than its intended purpose or if the above-mentioned conditions are not complied with: from the mistakes of İzersan Yapı Malz. San. VE TİC. LTD. ŞTİ. is not responsible.

All technical information stated in this product data sheet is based on laboratory tests. Actual values may vary due to circumstances beyond our control.

İZERSAN YAPI MALZ.SAN VE TİC.LTD.ŞTİ.

Center Factory: Egemenlik Mah. 6016/6 Sk. No:19/1 Işıkent Bornova/ İZMİR

www.dryfix.com.tr - info@izersan.com.tr

Tel&Fax: +90 850 777 05 35

